



# OmniSwitch Product Line Matrix

LAN products comparison guide

	Family	OmniSwitch 2260   2360	OmniSwitch 6360	OmniSwitch 6560	OmniSwitch 6465T	OmniSwitch 6465	OmniSwitch 6865	OmniSwitch 6570M	OmniSwitch 6860E/N	OmniSwitch 6900	OmniSwitch 9900
Class		SMB Value Stack	Value Stack	Value Stack	Extended Temp. Stack	Hardened Stack	Hardened Stack	Value Stack	Advanced Stack	Core Stack	Core Chassis
Hardware Limited Lifetime Warranty		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Max Capacity		180 Gbps	182 Gbps	304 Gbps	24 Gbps	128 Gbps	208 Gbps	210 Gbps	1020 Gbps	6.4 Tbps	25.6 Tbps / 51.2 Tbps
INTERFACES	RJ45 GigE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	MultiGig	✗	✓	✓	✗	✗	✗	✓	✓	✗	✓
	10Gbase-T	✗	✗	✗	✗	✗	✗	✗	✓	✓	✓
	SFP	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	SFP+	✓	✓	✓	✗	✓	✓	✓	✓	✓	✓
	SFP28	✗	✗	✗	✗	✗	✗	✗	✓	✓	✗
	QSFP+	✗	✗	✗	✗	✗	✗	✗	✓	✓	✓
	QSFP28	✗	✗	✗	✗	✗	✗	✗	✓	✓	✓
POE	PoE	✓	✓	✓	✓	✓	✓	✗	✓	✗	✓
	802.3bt	✗	✓	✓	✗	✓	✗	✗	✓	✗	✗
	Max PoE budget	740 W	760 W	1 645 W	115 W	285 W	300 W	✗	3 390 W	✗	10 800 W
	Fast or Perpetual PoE	✓	✓	✗	✗	✓	✓	✗	✓	✗	✗
REDUNDANCY	Power supply redundancy	✗	✗	✓	✗	✓	✓	✓	✓	✓	✓
	Alarm contacts	✗	✗	✗	✗	✓	✗	✗	✗	✗	✗
	Virtual Chassis Size	✗ 4	4	8	4	4	8	4	8	6	OS9907 2 / OS9912 <sup>1</sup>
	Max VFL speed	✗ 10G	10G	20G	1G	10G	20G	10G	100G	100G	100G
INDUSTRIAL	1588v2	✗	✗	✓	✓	✓	✓	✗	✓	✗	✗
	MACsec	✗	✗	✓	✓	✓	✗	✓	✓	✓	✓
	ERP	✗	✗	✓	✓	✓	✓	✓	✓	✓	✓
	MRP	✗	✗	✗	✓	✓	✓	✗	✗	✗	✗
AUTOMATION	ZTP	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Intelligent Fabric	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓
	IoT device profiling	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Programmability	✗	Rest / Python	Rest / Python	Rest / Python	Rest / Python	Rest / Python	Rest / Python	Rest / Python	Rest / Python	Rest / Python
SIZE	Height	1 RU	1 RU	1 RU	1 RU	4.4 - 15 cm	1 or 2 RU	1 RU	1 RU	1 RU	11/17.25 RU
	Switch Width	Half Rack or Full Rack	Half Rack or Full Rack	Full Rack	Half Rack	Din mount (8 cm) or Full Rack	Full Rack	Half Rack or Full Rack	Full Rack	Full Rack	Full Rack
	Depth	28 - 30 cm	22 - 33 cm	35 cm	28 cm	15 - 27 cm	26 - 27 cm	28 - 33.5 cm	35 - 44 cm	47 - 56 cm	58.4 cm
SCALABILITY	Max MAC capacity	16 K 32 K	16 K	16 K	16 K	16 K	48 K	32 K	81 K	228 K	128 K
	Max ARP capacity	256	256	1024	256	256	16 K	1024	48K	48K	24 K
	Max Route capacity	2 32	64	256	128	128	64 K	256	128 K	324 K	128 K
ROUTING	Static Route	✓	✓	✓	✓	Limited	✓	✓	✓	✓	✓
	RIP	✗	✗	✓	Limited	Limited	✓	✓	✓	✓	✓
	OSPF	✗	✗	Limited	✗	✗	✓	✗	✓	✓	✓
	BGP	✗	✗	✗	✗	✗	✓	✗	✓	✓	✓
VIRTUALIZATION	SPB	✗	✗	✗	✗	✗	✓	✗	✓	✓	✓
	VXLAN	✗	✗	✗	✗	✗	✗	✗	✓	✓	✓
	MPLS	✗	✗	✗	✗	✗	✗	✗	✓ <sup>1</sup>	✓ <sup>1</sup>	✓ <sup>1</sup>
DC	OVSDB	✗	✗	✗	✗	✗	✗	✗	✗	✓	✗
	RoCE	✗	✗	✗	✗	✗	✗	✗	✗	✓	✗
	Nutanix Support	✗	✗	✗	✗	✗	✗	✗	✗	✓	✗
MISC.	ISSU	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓
	DIN rail mounting	✗	✗	✗	✗	✓	✓	✗	✗	✗	✗
	DNV certified models	✗	✗	✓	✗	✓	✓	✗	✗	✓	✗

# Simplicity is a security feature

We believe the easier it is to operate and manage a network, the more secure it will be. Simplicity reduces the potential for errors which can leave areas vulnerable.

The ALE OmniSwitch takes simplicity to the next level with:

- Security by default
- Edge, hardened, core switches using the **same secure level code**
- **IoT automatic containment**
- **Micro-segmentation** & Zero-trust network architecture
- Deep Packet Inspection (DPI)
- **Single management system**, unified for OmniSwitches & OmniAccess Stellar WLAN solutions
- Operation at wire-rate speeds
- **Shortest Path Bridging (SPB)**
- Real-time management of remote operations using videos

## Alcatel-Lucent Enterprise delivers Ethernet Switches for today and tomorrow

<sup>1</sup> Support planned in future release

**RU** : Rack Unit

The feature support and the scalability may be different based on each model. Please refer to the datasheet and latest release note for the detail.

[www.al-enterprise.com](http://www.al-enterprise.com) The Alcatel-Lucent name and logo are trademarks of Nokia used under license by ALE. To view other trademarks used by affiliated companies of ALE Holding, visit: [www.al-enterprise.com/en/legal/trademarks-copyright](http://www.al-enterprise.com/en/legal/trademarks-copyright). All other trademarks are the property of their respective owners. The information presented is subject to change without notice. Neither ALE Holding nor any of its affiliates assumes any responsibility for inaccuracies contained herein. © Copyright 2020 ALE International, ALE USA Inc. All rights reserved in all countries. DID 21102903 (January 2024)

